

# Microcanner Mandatory Items

Training video on [Microcannerparts.com](https://Microcannerparts.com) (Password supplied in email after machine purchase)

<p><b>CONNECTIONS</b></p>	<ul style="list-style-type: none"> <li>● <a href="#">Air compressor equivalent to this</a></li> <li>● 12-gauge 110-volt HEAVY DUTY extension cord</li> <li>● <a href="#">A GFCI outlet to plug the machine into</a> (In some cases a GFCI does not work due to weak building grounds, in those cases <a href="#">please use a ELCI</a>)</li> <li>● A clean CO2 supply line with regulator and female air fitting</li> <li>● An air hose to run from the compressor to the machine</li> <li>● Air dryer (listed on page 2)</li> </ul>
<p><b>TANK AND SUPPLY REQUIRMENTS</b></p>	<ul style="list-style-type: none"> <li>● 15 PSI head pressure at bright tank or uni-tank</li> <li>● Beverage chilled to 34 degrees at the center of the tank</li> <li>● Beverage carbonated to 2.6 or less</li> <li>● PBW and parasitic acid to clean supply lines</li> </ul>
<p><b>SUPPLYS</b></p>	<ul style="list-style-type: none"> <li>● LOE 202 B64 Lids</li> <li>● Standard 12 or 16 ounce cans</li> <li>● Water resistant kitchen scale that measures in grams</li> <li>● Thermal pen or digital thermometer</li> </ul>
<p><b>ADDITIONAL ITEMS</b></p>	<ul style="list-style-type: none"> <li>● Cardboard</li> <li>● Pak tecks</li> <li>● Portable pack off table</li> <li>● <a href="#">Cart</a> (if desired, for Atomic only)</li> <li>● <a href="#">Conveyor</a> and <a href="#">conveyor instructions</a> (if desired, for Atomic only)</li> </ul>
<p><b>MAINTENANCE AND UPKEEP</b></p>	<ul style="list-style-type: none"> <li>● <a href="#">Food grade silicone spray for air cyliners</a></li> <li>● <a href="#">Food grade zero weight grease for operations</a></li> <li>● <a href="#">Grease gun</a></li> <li>● <a href="#">Digital calipers</a></li> <li>● <a href="#">Precision screwdrivers</a></li> <li>● <a href="#">Wire strippers</a></li> <li>● <a href="#">Adjustable Wrench</a> (Needs to open to at least 1-1/8")</li> <li>● <a href="#">Wrench set</a></li> <li>● <a href="#">Hex key set</a></li> <li>● <a href="#">Bucket</a> (Atomic only)</li> <li>● <a href="#">Submersible pump</a> (Atomic only)</li> <li>● <a href="#">Leader hose</a> (Atomic only)</li> <li>● <a href="#">Tri clamp connector with 1/2" barb fitting</a> (Atomic only)</li> <li>● <a href="#">Hose clamp</a> (Atomic only)</li> <li>● Pump assembly instructions (Atomic only):             <ol style="list-style-type: none"> <li>1. Connect the female end of leader hose to the submersible pump.</li> <li>2. Cut off the male end of the leader hose</li> <li>3. Insert the barb of the tri clamp fitting into the cut end of the leader hose and secure the hose clamp</li> </ol> </li> </ul>



**RAPID CONTROL SERVICE, INC**

**PARTNERS IN AUTOMATION SINCE 1964**

**PNEUMATIC | ELECTRICAL | ASSEMBLY SYSTEMS  
RESISTANCE WELDING**



## **IDFB3E-11N, Refrigerated Air Dryer, Standard Inlet Air Temperature for North America**

Series IDFB3E-11N refrigerated air dryers are suitable for use in aftercooled systems with compressors up to ~100 hp (depending on dew point desired).

These durable units have simple control systems and are easily serviced.

- UL certified for use in North America
- 60 Hz operation
- Max. inlet air temperature: 122°F (50°C)
- Max. flow at rated conditions: 300 scfm  
510m<sup>3</sup>/hr (ANR) @37°F (3°C) PDP



**Special price for Microcanner clients:**

**\$571.95**

*List price \$780*

*Price available on credit card orders only*

*Product normally in stock, item ships FedEx Ground, freight added to invoice*

**Rapid Control Service, Inc.**

**2479 28th Street, SW**

**Grand Rapids, MI 49519**

**800.632.1857, ask for sales**

**www.rapidcontrol.com**

**Email: sales@rapidcontrol.com**

