

Microcanner Mandatory Items

Training video on Microcannerparts.com

<p>CONNECTIONS</p>	<ul style="list-style-type: none"> ● Air compressor equivalent to this ● 12-gauge 110-volt HEAVY DUTY extension cord ● A GFCI outlet to plug the machine into (In some cases a GFCI does not work due to weak building grounds, in those cases please use a ELCI) ● A clean CO2 supply line with regulator and female air fitting ● An air hose to run from the compressor to the machine ● Air dryer (listed on page 2)
<p>TANK AND SUPPLY REQUIREMENTS</p>	<ul style="list-style-type: none"> ● 15 PSI head pressure at brite tank or unitank ● Beverage chilled to 34 degrees at the center of the tank ● Beverage carbonated to 2.6 or less ● PBW and peracetic acid to clean supply lines
<p>SUPPLIES</p>	<ul style="list-style-type: none"> ● LOE 202 B64 Lids ● Standard 12 or 16 ounce cans ● Water resistant kitchen scale that measures in grams ● Thermal pen or digital thermometer
<p>ADDITIONAL ITEMS</p>	<ul style="list-style-type: none"> ● Cardboard ● PakTechs ● Portable pack off table ● Cart (if desired, for MC-ATOMIC only) ● Conveyor and conveyor instructions (if desired, for MC-ATOMIC only)
<p>MAINTENANCE AND UPKEEP</p>	<ul style="list-style-type: none"> ● Food grade silicone spray for air cylinders ● Food grade zero weight grease for operations ● Grease gun ● Digital calipers ● Precision screwdrivers ● Wire strippers ● Adjustable Wrench (Needs to open to at least 1-1/8") ● Wrench set ● Hex key set ● Bucket (MC-ATOMIC only) ● Submersible pump (MC-ATOMIC only) ● Leader hose (MC-ATOMIC only) ● Tri clamp connector with 1/2" barb fitting (MC-ATOMIC only) ● Hose clamp (MC-ATOMIC only) ● Pump assembly instructions (Atomic only): <ol style="list-style-type: none"> 1. Connect the female end of leader hose to the submersible pump. 2. Cut off the male end of the leader hose 3. Insert the barb of the tri clamp fitting into the cut end of the leader hose and secure the hose clamp



RAPID CONTROL SERVICE, INC

PARTNERS IN AUTOMATION SINCE 1964

**PNEUMATIC | ELECTRICAL | ASSEMBLY SYSTEMS
RESISTANCE WELDING**



IDFB3E-11N, Refrigerated Air Dryer, Standard Inlet Air Temperature for North America

Series IDFB3E-11N refrigerated air dryers are suitable for use in aftercooled systems with compressors up to ~100 hp (depending on dew point desired).

These durable units have simple control systems and are easily serviced.

- UL certified for use in North America
- 60 Hz operation
- Max. inlet air temperature: 122°F (50°C)
- Max. flow at rated conditions: 300 scfm
510m³/hr (ANR) @37°F (3°C) PDP



Special price for Microcanner clients:

\$571.95

List price \$780

Price available on credit card orders only

Product normally in stock, item ships FedEx Ground, freight added to invoice

Rapid Control Service, Inc.

2479 28th Street, SW

Grand Rapids, MI 49519

800.632.1857, ask for sales

www.rapidcontrol.com

Email: sales@rapidcontrol.com

